

型号	内径		外径		宽				半径		额定载荷		重量
Bearing No.	Bore		Outer Diameter		Width				Radius		Load Rating(KN)		Weight
	d		D		open		sealed		r		Dynamic Cr动	Static Cor静	(kg)
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch			
	R156	4.763	0.1875	7.938	0.3125	2.78	0.1094	3.18	0.125	0.1	.0004		
R166	4.763	0.1875	9.525	0.375	3.18	0.125	3.18	0.1250	0.1	0.004	-	-	0.0008
R3	4.762	0.1875	12.7	0.5	3.969	0.1562	4.980	0.196	0.3	0.012	1.01	0.48	0.0022
R3a	4.762	0.1875	12.7	0.5	4.978	0.196	4.98	0.1960	0.3	0.012	1.31	0.485	0.0025
R168	6.35	0.25	9.525	0.375	3.18	0.125	3.18	0.125	0.1	0.004	-	-	0.0006
R188	6.35	0.25	12.7	0.5	3.18	0.125	4.76	0.1875	0.15	0.006	-	-	0.0016
R4	6.35	0.25	15.875	0.625	4.978	0.196	4.980	0.196	0.3	0.012	1.136	0.558	0.005
R4A	6.35	0.25	19.05	0.75	5.556	0.2188	7.144	0.2821	0.4	0.016	2.175	1.136	0.008
R6	9.525	0.375	22.225	0.875	5.556	0.2188	7.144	0.2821	0.4	0.016	2.56	1.35	0.011
R8	12.7	0.5	28.575	1.125	6.35	0.25	7.938	0.3125	0.4	0.03	3.93	2.23	0.018
R8-7	11.113	0.4375	28.575	1.125	6.35	0.25	--		0.4	0.016	4.62	2.79	0.015
R10	15.875	0.625	34.925	1.375	7.144	0.2812	8.731	0.3438	0.8	0.03	-	-	0.037
99502H	15.875	0.625	34.925	1.375	-	-	11	0.4331	0.8	0.03	4.62	2.79	0.042
R12	19.05	0.75	41.275	1.625	7.938	0.3125	11.113	0.4375	0.8	0.03	7.24	4.463	0.047
R14	22.225	0.875	47.625	1.875	9.626	0.3705	12.700	0.5	0.8	0.03	7.74	4.96	0.072
R16	25.4	1	50.8	2	9.525	0.3705	12.7	0.5000	0.8	0.03	7.74	5.16	0.085
R18	28.575	1.125	53.975	2.125	9.525	0.3705	12.7	0.5000	0.8	0.03	10.18	6.91	0.09
R20	31.75	1.25	57.15	2.25	9.525	0.3705	12.7	0.5000	0.8	0.03	10.8	7.52	0.095
R22	34.925	1.375	63.5	2.5	11.112 0.4375		14.288	0.5625	0.8	0.03	12.28	8.5	0.105
R24	38.1	1.5	63.5	2.625	11.112	0.4375	14.288	0.5625	0.8	0.03	14.35	10.24	0.12