

型号	内径		尺寸								额定载荷		重量(kg)
Unit No.	Shaft Dia		Dimensions(mm)								Rating Load		Mass(kg)
	d		D	B	C	S	S1	G	h	ds	动态额定负荷	静态额定负荷	
	in	mm									Dynamic Cr	Static Cor	
UC202		15										0.12	■
RB202-10	5/8		40	27.4	14	11.5	15.9	4.5	3.5	M5X0.8	9550	0.12	■
203		17	1.5748	1.0787	0.5S12	0.4528	0.6260	0.1772	0.1378	10 #-32UNF		0.11	-
203-11	11/16											0.11	■
UC204-12	3/4	20	47	31	16	12.7	18.3	4.7	4.4	M6X1	12800	0.18	0.19
RB204			1.8540	1.220S	0.6293	0.5000	0.7205	0.1850	0.1732	1/4-28UNF		0.17	0.18
UC205-14	1-7/8	25	52	34	17	14.3	19.7	5.5	4.3	M6X1	14000	0.23	0.26
RB205-15	15/16		2.0472	1.3386	0.6693	0.5630	0.7756	0.2165	0.1693	1/4-28UNF		0.22	0.25
205												0.21	0.24
205-16	1											0.20	0.23
UC206-10	1-V8	30	62	38.1	19	15.9	22.2	5.5	5	M6X1		0.34	0.38
RB206			2.4409	1.5000	0.7480	0.6260	0.8740	0.216S	0.1969	1/4-28UNF	19500	0.32	0.36
206-19	1-3/16											0.31	0.35
206-20	1-1/4											0.30	0.34
UC207-20	1-1/4	35	72	42.9	20	17.5	25.4	6.5	5.8	M8X1		0.53	0.61
RB207-21	1-5/16		2.8346	1.6890	0.7874	0.6890	1.0000	0.2559	0.2283	5/16-24UNF	25700	0.51	0.59
207-22	1-3/8											0.48	0.56
207												0.47	0.54
207-23	1-7/16											0.45	0.52
UC208-24	1-1/2		80	49.2	21	19	30.2	8	6.3	MdXI		0.66	0.76
RB208-25	1-9/16	40	3.1496	1.9370	0.8266	0.7460	1.1690	0.3150	0.2480	5/16-24UNF	29600	0.65	0.74
208												0.64	0.73
UC209-26	1-5/8	45	85	49.25	22	19	30.2	8	6.8	M8X1		0.78	0.88
RB209-27	1-11/16		3.346S	1.9370	0.6661	0.7480	1.1890	0.3150	0.2677	5/16-24UNF	31850	0.74	0.85

209-28	1-3/4											0.70	0.01
209		50	90	51.6	23	19	32.6	9	6.5	M10X1.25		0.68	0.79
UC210-30	1-7/8		3.5433	2.0315	0.9055	0.7460	1.2835	0.3543	0.2559	3/6-24UNF	35100	0.87	0.96
RB210-31	1-15/16											0.62	0.93
210												0.80	0.90
210-32	2											0.78	■
UC211-32	2		100	55.6	25	22.2	33.4	9	7.2	M10X1.25	43550	1.27	1.40
RB211-37	2-1/8	55	39370	2.1890	0.9843	0.8740	1.3150	0.3543	0.2835	3/6-24UNF		1.17	1.30
211												1.12	1.24
211-35	2-3/16											1.10	1.22
UC212-36	2-V4	60	110	65.1	27	25.4	39.7	10.5	8.2	M10X1.25		1.67	1.86
RB212			4.3307	2.5630	1.0630	1.0000	1.5630	0.4134	0.3226	3/0-24UNF	47800	1.53	1.74
212-30	2-3/B											1.53	1.72
212-39	2-7/16											1.45	1.65
UC213-40	2-1/2	65	120	65.1	28	25.4	39.7	12	6	M12X1.25	57200	1.94	
213			4.7244	2.5630	1.1024	10000	1.5630	0.4724	0.3150	7/16-20UNF		1.86	
UC214-44	2-3/4		125	74.9	30	30.2	44.4	12	9	M12X1.25	60800	2.06	
214		70	4.9213	2.93.7.	1.1811	1.1890	1.7460	0.4724	0.3543	7/16-20UNF		2.05	■
UC215-47	2-15/16	75	130	77.8	30	33.3	44.5	12	9	M12X1.25	66000	2.30	
215			5.1181	3.0630	1.1811	1.3110	1.7520	0.4724	0.3543	7/16-20UNF		2.21	
215-48	3											2.13	
UC216		80	140	82.6	33	33.3	49.3	14	10.3	M12X1.25	71500	2.79	■
			5.5118	3.2520	1.2992	1.3110	1.9410	0.5512	0.4055	7/16-20UNF			
UC217-52	3-1/4		150	55.7	35	34.1	51.6	14	11	M12X1.25	83200	3.60	
217		85	5.9055	3.3740	1.3780	1.3425	2.03 IS	0.5512	0.4331	7/16-20UNF		3.38	
UC218-56	3-1/2	90	160	96	37	39.7	56.3	14	12	M12X1.25		4.56	
218			6.2992	3.7795	1.4567	1.5630	2.2165	0.5512	0.4724	1/2-20UNF		4.45	